

Made in the **United States** of America

Accessories:
Everything you'll need.



A1

A2


A3

A1. 45P Muzzle Break/Thread Protector
45APC/9MM Pistol – Specify Thread

A2. Silencer Adapter/Muzzle Break
AR15 = 1/2-28 AR10 = 5/8-24
Included with ALL Rifle/R Models –
Specify Other Thread

A3. Thread Protector/Muzzle Break
45APC/9MM Pistol – Specify Thread

Finish Options:



Anodized
Aluminum

Flat
Black

Flat Dark
Earth

Optional Cerakote Coating
available.

We're constantly adding new items to our product line!

MODEL: 175-6-556R – Shown on front cover; Designed specifically for Police Depts.

Call (215) 949-8378 or check our website for updated information.

ABOUT US:



3 Ring Silencer Corporation

1016 Branagan Drive
Tullytown, PA 19007

Phone: (215) 949-8378

Fax: (215) 949-8373

www.3RingSilencer.com

3 Ring Silencer Corporation was founded on a lifetime of interest and enthusiasm in all things gun related. As an avid gun collector with a love of shooting and a 25+ year background in the manufacturing industry, producing silencers was a natural next step.

In our development process we worked to improve the properties of many existing suppressor systems and we ultimately developed a variety of our own designs and versions.

We continue to research and develop our suppressors trying to bring them closer to the ideal.

Along the way, we have made the necessary modifications to improve ourselves and our products. 3 Ring Silencer's suppressors begin with first impressions and quality you can see and touch. The front and rear of the suppressor tube features impeccable knurling which aids installation and removal. The knurling is also handy when field-stripping the suppressors recoil booster device. Knurling on pistol suppressors is rare but we pride ourselves in taking this extra effort.

Our innovative team never rests and we are constantly setting new goals for ourselves.

F R E E D O M



Great Silencer, Great Price

SILENCE...
IS GOLDEN

Price: \$1.95

 **3 RING SILENCER**
CORPORATION

 **3 RING SILENCER**
CORPORATION

©2017 3 Ring Silencer Corp. • 17-1457TRS-BRO-07

Pistol Models:
Light and Quiet.

Piston Included with ALL Pistol/P Models



MODEL: 125-9-9P
CALIBERS: 9MM and Lower Semi-Auto Pistol
MATERIAL: Aluminum
LENGTH: 9.5"
WEIGHT: 11 oz.
DIAMETER: 1.25"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28
AVERAGE SUPPRESSION: Up to 30 dB Subsonic



MODEL: 125-9-45P
CALIBERS: 45APC and Lower Semi-Auto Pistol
MATERIAL: Aluminum
LENGTH: 9.5"
WEIGHT: 11 oz.
DIAMETER: 1.25"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28
AVERAGE SUPPRESSION: Up to 25 dB



MODEL: 150-9-9P
CALIBERS: 9MM and Lower Semi-Auto Pistol
MATERIAL: Aluminum
LENGTH: 9.5"
WEIGHT: 15 oz.
DIAMETER: 1.50"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28
AVERAGE SUPPRESSION: Up to 33 dB Subsonic



MODEL: 150-9-45P
CALIBERS: 45APC and Lower Semi-Auto Pistol
MATERIAL: Aluminum
LENGTH: 9.5"
WEIGHT: 15 oz.
DIAMETER: 1.50"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28
AVERAGE SUPPRESSION: Up to 29 dB

Over The Barrel Models:
Our Most Powerful.



MODEL: OTB-175-X-7-762R
CALIBERS: 7.62x51 (308) & Lower Semi-Auto
MATERIAL: Aluminum
LENGTH: 11" - 13" Total
 X=4 Over Barrel = 4"
 X=5 Over Barrel = 5"
 X=6 Over Barrel = 6"
 Past Barrel = 7"
WEIGHT: 18-20 oz.
DIAMETER: 1.75"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28
AVERAGE SUPPRESSION: TBD



MODEL: OTB-200-X-7-762R
CALIBERS: 7.62x51 (308) & Lower Semi-Auto
MATERIAL: Aluminum
LENGTH: 11" - 13" Total
 X=4 Over Barrel = 4"
 X=5 Over Barrel = 5"
 X=6 Over Barrel = 6"
 Past Barrel = 7"
WEIGHT: 19-22 oz.
DIAMETER: 2.00"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28
AVERAGE SUPPRESSION: TBD



QUIET
IS ALWAYS THE BEST OPTION

Rifle Models:
Best Suppression.

* Silencer Adapter/Muzzle Break Included with ALL Rifle/R Models See Back Page - A2.



MODEL: 175-9-762R
CALIBERS: 7.62x51 (308) & Lower Semi-Auto
MATERIAL: Aluminum
LENGTH: 9.5"
WEIGHT: 18 oz.
DIAMETER: 1.75"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28*
AVERAGE SUPPRESSION: Up to 30dB Subsonic



MODEL: 200-9-762R
CALIBERS: 7.62x51 (308) & Lower Semi-Auto
MATERIAL: Aluminum
LENGTH: 9.5"
WEIGHT: 27 oz.
DIAMETER: 2.00"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28*
AVERAGE SUPPRESSION: Up to 35dB Subsonic



MODEL: 175-12-762R
CALIBERS: 7.62x51 (308) & Lower Semi-Auto
MATERIAL: Aluminum
LENGTH: 12"
WEIGHT: 27 oz.
DIAMETER: 1.75"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28*
AVERAGE SUPPRESSION: Up to 35dB Subsonic



MODEL: 200-12-762R
CALIBERS: 7.62x51 (308) & Lower Semi-Auto
MATERIAL: Aluminum
LENGTH: 12"
WEIGHT: 32 oz.
DIAMETER: 2.00"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28*
AVERAGE SUPPRESSION: Up to 40dB Subsonic



MODEL: 225-9-762R
CALIBERS: 7.62x51 (308) & Lower Semi-Auto
MATERIAL: Aluminum
LENGTH: 9.5"
WEIGHT: 35 oz.
DIAMETER: 2.25"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28*
AVERAGE SUPPRESSION: Up to 40dB Subsonic



MODEL: 225-12-762R
CALIBERS: 7.62x51 (308) & Lower Semi-Auto
MATERIAL: Aluminum
LENGTH: 12"
WEIGHT: 38 oz.
DIAMETER: 2.25"
MOUNTS: Direct Thread
THREADS: Choice of 1/2-28, 5/8-24, 9/16-24, 37/64-28*
AVERAGE SUPPRESSION: Up to 45dB Subsonic